CELCURE AC-500 TREATED TIMBER



Page: 1

Compilation date: 21/10/2009

Revision date: 09/02/2018

Revision No: 7

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: CELCURE AC-500 TREATED TIMBER

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Protim Solignum Ltd

Fieldhouse Lane

Marlow

Buckinghamshire

SL7 1LS

United Kingdom

Tel: +44 (0) 1628 486 644 **Fax:** +44 (0) 1628 476 757

Email: kpc@koppers.eu

1.4. Emergency telephone number

Emergency tel: +44 (0) 1628 890 907

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 2: H411; Eye Irrit. 2: H319

Most important adverse effects: Causes serious eye irritation. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

Hazard pictograms: GHS07: Exclamation mark

GHS09: Environmental





Signal words: Warning

Precautionary statements: P261: Avoid breathing dust.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P305: IF IN EYES:

CELCURE AC-500 TREATED TIMBER

Page: 2

P352: Wash with plenty of water.

P337+313: If eye irritation persists: Get medical attention.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

SOFT WOOD DUST

EINECS	CAS	PBT / WEL	CLP Classification	Percent		
-	-	Substance with a Community workplace exposure limit.	-	70-90%		
COPPER(II) CARBONATE-COPPER(II) HYDROXIDE (1:1)						

- 12069-69-1 - Acute Tox. 4: H302+332; Eye Irrit. 2: <1% H319; Aquatic Acute 1: H400; Aquatic Chronic 1: H410

BORIC ACID

233-139-2	10043-35-3	-	Repr. 1B: H360FD	<1%	

QUATERNARY AMMONIUM COMPOUNDS, BENZYL (C12-C16) ALKYL DIMETHYL, CHLORIDES

270-325-2	68424-85-1	-	Acute Tox. 4: H302; Skin Corr. 1B:	<1%
		H314; Eye Dam. 1: H318; Aquatic		
			Acute 1: H400; Aquatic Chronic 1:	
			H410	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

CELCURE AC-500 TREATED TIMBER

Page: 3

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate

method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Do not handle in a confined space. Avoid the formation or spread of dust in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep treated timber dry. Store freshly treated timber

within a bunded area to prevent escape of treatment product into the environment until

dry.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

CELCURE AC-500 TREATED TIMBER

Page: 4

Hazardous ingredients:

SOFT WOOD DUST

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	5 mg/m3	-	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: When sawing wood: Respiratory protective device with particle filter.

Hand protection: Protective gloves.

Eye protection: When sawing wood: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Solid

Colour: Pale green

Odour: Odourless when dry

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

CELCURE AC-500 TREATED TIMBER

Page: 5

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

COPPER(II) CARBONATE-COPPER(II) HYDROXIDE (1:1)

ORAL	DAT	LD50	1350	ma/ka
URAL	KAI	LD50	1350	mg/kg

QUATERNARY AMMONIUM COMPOUNDS, BENZYL (C12-C16) ALKYL DIMETHYL, CHLORIDES

ORL	RAT	LD50	344	ma/ka

Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

COPPER(II) CARBONATE-COPPER(II) HYDROXIDE (1:1)

Daphnia magna	48H EC50	25.0	μg/l	l
---------------	----------	------	------	---

QUATERNARY AMMONIUM COMPOUNDS, BENZYL (C12-C16) ALKYL DIMETHYL, CHLORIDES

-	48H EC50	0.025	mg/l
BLUEGILLS	96H LC50	0.515	mg/l
RAINBOW TROUT	96H LC50	0.93	mg/l

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

CELCURE AC-500 TREATED TIMBER

Page: 6

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H302: Harmful if swallowed.

H302+332: Harmful if swallowed or if inhaled.

H314: Causes severe skin burns and eye damage.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H360FD: May damage fertility. May damage the unborn child.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

CELCURE AC-500 TREATED TIMBER

Page: 7

and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.